Changes to the third edition following January 2012 update

Section Page Amendment

Introduction

Table 2	3	New floor reference E-FC-14 $^{\text{TM}}$ added.
Table 3a	4	New floor reference E-FC-14 $^{\rm TM}$ added; and notes amended.
Table 5	6	New floor reference E-FC-14™ added.

Table 6b 8 New floor reference E-FC-14[™] added.

Table 7 9 New floor reference E-FC-14[™] added.

Separating Wall - Masonry

E-WM-12™

Cavity 1 Cavity insulation option added. insulation

E-WM-17™

4th bullet point	1	Amended to include the use of hollow or cellular blocks.
Hollow or cellular blocks	1	Hollow or cellular blocks option added.
Diagram 1	2	Hollow or cellular blocks option added for inner leaf construction.
Diagram 2	2	Hollow or cellular blocks option added for inner leaf construction.

Check point added to cover hollow or

cellular blocks option.

Separating Wall – Timber

E-WT-2TM

Checklist

Diagram 6	5	Repositioned from page 4.
Diagram 8	6	Repositioned from page 5.
Diagram 9	6	New room-in-roof flanking junction added.
Diagram 10	7	Repositioned from page 6.

Separating Floor – Concrete

E-FC-14™

All 1-6 New robust detail™ added – Floating screed applied to Thermal Economics IsoRubber Code layer on precast planks.

Separating Floor – Timber

E-FT-1TM

Joists	1	Minimum depth reduced from 240mm.
Checklist	6	Point 1 amended to reflect revised minimum depth.

E-FT-6™

Joist types 1 Three further joist types added.

Appendix A1

- de le constant				
Contents	1	Room-in-roof section re-titled to remove masonry wall reference.		
Room-in- roof section	5	Masonry wall references removed.		
Room-in- roof diagram	5	Insulation requirement added for timber frame applications.		