Changes to the third edition following October 2012 update

Table 1	2	New wall reference E-WM-24 [™] added.
Table 2	3	New floor reference E-FC-15 [™] added.
Table 3a	4	New wall reference E-WM-24™ added with valid combinations.
Table 3a	4	New floor reference E-FC-15 [™] added with valid combinations.
Table 3a	4	Note 2 added.
Table 4	6	New wall reference E-WM-24 [™] added.
Table 5	6	New floor reference E-FC-15 [™] added.
Table 6a	7	New wall reference E-WM-24 [™] added. New note 1 added, referenced by E-WM-19 [™] , E-WM-23 [™] and E-WM-24 [™] .
Table 6b	8	New floor reference E-FC-15 [™] added.
Table 7	9	New floor reference E-FC-15 [™] added.

Separating Wall – Masonry

Page Amendment

E-WM-22™

Section

Introduction

Isometric Block density	1	New block added – Plasmor Aglite Ultima 1050 kg/m³.		
Diagram 1	2	New block added – Plasmor Aglite Ultima 1050 kg/m³.		
Diagram 2	2	New block added – Plasmor Aglite Ultima 1050 kg/m³.		
Checklist	6	New block added to point 3 – Plasmor Aglite Ultima 1050 kg/m ³ .		
E-WM-23™				
Top bullet point	1	Standard and thin joint methods added.		
Isometric Wall ties	1	Thin joint tie specification added.		

Checklist	6	Thin joint tie specification added to
		point 6.

E-WM-24™

All 1-6 New robust detail[™] added – Aircrete wall with 100mm cavity insulated with Saint Gobain-Isover RD Party Wall Roll, and gypsum board finish.

Separating Floor – Concrete

E-FC-15™

All 1-6 New robust detail[™] added – Floating screed applied to 'Regupol Quietlay' on precast planks. Section Page Amendment

Appendix A2

Diagram 3	2	150mm (min) dimension deleted from raft.
ltem 'e'	2	150mm (min) dimension and Insulslab SFRC reference added.

Appendix A3

Isometric	3	Trays amended to show interlocking arrangement.
Option 2	3	Joist type amended.
Contact details	3	Telephone, fax and email details amended.